

REMARKS

This Preliminary Amendment cancels, without prejudice, claims 1 to 10 in the underlying PCT Application No. PCT/EP2003/011617 and adds new claims 11 to 21. The new claims, inter alia, conform the claims to United States Patent and Trademark Office rules and does not add any new matter to the application.

In accordance with 37 C.F.R. § 1.125(b), the Substitute Specification (including the Abstract) contains no new matter. The amendments reflected in the Substitute Specification (including Abstract) are to conform the Specification and Abstract to United States Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. §§ 1.121(b)(3)(ii) and 1.125(c), a Marked-Up Version of the Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. Approval and entry of the Substitute Specification (including Abstract) are respectfully requested.

The underlying PCT Application No. PCT/EP2003/011617 includes an International Search Report, dated March 11, 2004, a copy of which is included. The Search Report includes a list of documents that were considered by the Examiner in the underlying PCT application.

It is respectfully submitted that the subject matter of the present application is new, non-obvious and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully submitted,

KENYON & KENYON

Dated: May 26, 2005

By: Richard L. Mayer
Richard L. Mayer
Reg. No. 22,490
One Broadway
New York, New York 10004
(212) 425-7200
CUSTOMER NO. 26646

CUP HOLDER

FIELD OF THE INVENTION

The **present** invention relates to a cup holder for a motor vehicle ~~according to the precharacterizing clause of patent claim 1.~~

5

BACKGROUND INFORMATION

[[DE]] **German Published Utility Model No. 89 11 649** [[U1]]

~~discloses~~ **describes** a cup holder for a motor vehicle that is fitted into an existing duct of an air-conditioning system of the motor vehicle. A fan of the air-conditioning system generates an air flow which is conveyed via air-directing devices to a beverage container which is retained in a receiving device arranged in the duct of the air-conditioning system. The receiving device is an opening which is introduced in the duct of the air-conditioning system and can be closed by a lid.

When the lid is open, a beverage container can be inserted into the receiving device, so that the air conveyed by the fan flows around the beverage container. Since the beverage container has to be arranged directly in the air flow, i.e., in the duct of the air-conditioning system, the cup holder may, under some circumstances, be arranged in the vehicle at a location to which access is difficult for the occupant.

25

SUMMARY

~~It is therefore the object~~ **According to an example embodiment** of the **present** invention, ~~to provide~~ a cup holder **is provided** which ~~can~~ **may** be arranged in a vehicle independently of the position of the air-conditioning system.

30

~~The object is achieved according to the invention by the features of patent claim 1.~~

The cup holder ~~has~~ may have a receiving device which ~~can~~ may
5 be pulled out from a housing. The housing is connected to the
air-conditioning system, so that the air flow of the air-
conditioning system ~~can~~ may be directed directly into the
receiving device. If a beverage container is now to be
introduced into the cup holder, then the receiving device is
10 pulled out from the housing while remaining connected to the
air-conditioning system, and the beverage container is
inserted. If the cup holder is no longer required, the
receiving device ~~can~~ may be pushed again into the housing.
Since the beverage container does not have to be arranged
15 directly in the air flow of the air-conditioning system, the
cup holder ~~according to the invention can~~ may be arranged
virtually anywhere in a motor vehicle.

An air-directing device ~~can~~ may be integrated in the receiving
20 device and ~~directs~~ may direct the air flow conveyed by the
air-conditioning system as far as a retaining opening
introduced into the receiving device.

In ~~one preferred~~ an example embodiment, the air-introducing
25 device ~~has~~ may have two inflow ducts which lead into an
annular duct around the retaining opening. The retaining
opening of the receiving device is formed by a cylindrical
wall into which discharge openings are introduced. The air of
the air-conditioning system ~~can~~ may therefore flow via the two
30 inflow ducts into the annular duct and ~~can~~ may emerge through
the outflow openings and ~~can~~ may flow around the beverage
container retained in the retaining opening.

An inlet opening which, for example, is provided with a
35 connecting branch ~~can~~ may be introduced into the housing. A

connecting duct which connects the air-conditioning system and the inlet opening to each other is connected to the connecting branch. In the not-in-use position of the cup holder, a rear wall of the receiving device ~~can~~ may close the inlet opening.

5

In order to avoid flow loss, a seal ~~can~~ may be arranged between the rear wall and a wall region of the housing, which wall region surrounds the inlet opening, which seal, in the not-in-use position, is pressed by the rear wall of the receiving device against the wall region.

10

In order to temper optionally warm or hot beverage containers, the connecting duct ~~can~~ may be connected by a first connection to an evaporator and by a second connection to a heat exchanger of the air-conditioning system. A switch arranged in the connecting duct ~~can~~ may be activated, for example, by a stepping motor, so that the user ~~can~~ may connect either the first or the second connection.

15

20 ~~One preferred embodiment~~ Example embodiments of the present invention ~~is~~ are explained below with reference to the drawing, in which appended Figures.

BRIEF DESCRIPTION OF THE DRAWINGS

25 Fig. 1 ~~shows~~ is a ~~cross-section~~ cross-sectional view of a cup holder[[,]].

30

Fig. 2 ~~shows~~ is a ~~sectional illustration according to~~ cross-sectional view taken long the line II-II illustrated in Fig. 1[[,]].

Fig. 3 ~~shows~~ is a ~~sectional illustration of~~ cross-sectional view taken along line III-III illustrated in Fig. 1, and.

Fig. 4 ~~shows a diagrammatic illustration~~ is a schematic view of an air-conditioning system of a motor vehicle.

DETAILED DESCRIPTION

5 The cross-sectional ~~illustration in~~ view of Fig. 1 shows illustrates a cup holder C having a housing 1 in which a receiving device 2 is mounted displaceably in accordance with arrow A. The housing 1 is of box-shaped design and has an opening 3 on the front side, two side walls 6 and 7 arranged
10 parallel to each other and a rear end wall 8. The side walls 6 and 7 and the rear end wall 8 are connected to one another by an upper covering 4 and a base 5 (cf. Fig. 2). An inlet opening 9 from which a connecting branch 10 protrudes is introduced into the rear end wall 8. Two stops 11 and 12
15 protrude from the insides of the side walls 6 and 7 into the interior of the housing 1.

A retaining opening 13 is introduced into the receiving device 2. The retaining opening 13 is formed by a cylindrical wall
20 14 of the receiving device 2 and serves for the insertion of a beverage container ~~(not illustrated)~~.

An air-directing device 15 which has two inflow ducts 16 and 17 is integrated in the receiving device 2. The inflow ducts
25 16 and 17 lead into an annular duct 18 which surrounds the cylindrical wall 14 of the retaining opening 13. Discharge openings 19 are arranged in the cylindrical wall 14. The air L flowing in through the inflow ducts 16 and 17 is therefore directed by the air-directing device 15 to the annular duct 18
30 and flows there through the discharge openings 19 into the retaining opening 13.

The receiving device 2 has a rear wall 20 which closes the inlet opening 9 of the housing 1 when the receiving device 2
35 is retracted.

A seal 22 arranged between the rear wall 20 and a wall region 21 of the housing 1, which wall region surrounds the inlet opening 9, ~~ensures~~ may ensure that the air generated by the air-conditioning system ~~cannot~~ may not flow into the receiving device 2 as long as the cup holder C is in the not-in-use position.

The receiving device 2 has fittings 23 and 24 on both sides which, together with the stops 11 and 12 of the housing 1, form an extension limit. So that, in the extended state of the receiving device 2, no flow losses may occur between the housing 1 and receiving device 2, a seal 25 is arranged between the stops 11 and 12 and the fittings 23 and 24. The extended state of the receiving device 2 is indicated by chain-dotted line.

As ~~emerges from~~ illustrated in the ~~sectional illustration in~~ cross-sectional view of Fig. 3, the air L of the air-conditioning system flows out of the discharge openings 19 and along the beverage container 26 introduced into the retaining opening. For this purpose, the discharge openings 19 are introduced both on the upper side and on the lower side of the cylindrical wall 14. In order to achieve an optimum flow, an insert 27 ~~can~~ may be provided, so that between the beverage container 26 and the insert 27 an air gap 28 is formed into which the air L ~~can~~ may flow in accordance with the illustrated arrows ~~drawn in~~.

Fig. 4 ~~diagrammatically~~ schematically illustrates an air-conditioning system 29. The air-conditioning system 29 ~~comprises~~ includes an evaporator 30 and a heat exchanger 31. The evaporator 30 generates cold air L_K while the heat exchanger 31 heats warm air L_W . A connecting duct 32 is connected to the air-conditioning system 29 by a first

connection 33 and a second connection 34. The first connection 33 is connected to the evaporator 30 and the second connection 34 is connected to the heat exchanger 31. A switch 35 is arranged in the connecting duct 32 and is activated by a stepping motor M, so that either the first connection 33, i.e., cold air L_K , or the second connection 34, i.e., warm air L_W , is connected.

The air flow L generated is directed to the connecting branch 10 via the connecting duct 32.

The switch 35 is activated by the occupant, for example, by actuating a switch in the motor vehicle interior, so that he can may select warm air L_W or cold air L_K as a function of the inserted beverage container 26.

Abstract

ABSTRACT

~~The invention relates to a~~ **A** cup holder for a motor vehicle, having **includes** a receiving device (2) and a tempering device
5 which is connected to an air-conditioning system (29). The air-conditioning system (29) generates an air flow which is conveyed via an air-directing device (15) to a beverage container (26) which is retained in the receiving device (2).

10 In order to provide a cup holder which is easily accessible to an occupant and ~~can~~ **may** be tempered at the same time, ~~it is proposed that~~ the receiving device (2) ~~can~~ **may** be pulled out of a housing (1) while remaining connected to the air-conditioning system (29).

15

~~(Fig. 1)~~